


Description:

POLYONICS 300 is a high temperature, solvent, acrylic, pressure sensitive adhesive provided with two release liners.

**Features:**

- Solvent Acrylic
- Higher heat resistance
- Works well in humid environments
- Good shear
- Plasticizer and solvent resistant
- REACH and RoHS compliant

Applications:

Ideal for bonding materials that will tolerate high temperatures, chemical exposure, and humidity. This adhesive system has a proven track record as an adhesive for tapes and labels used in printed circuit board assembly applications.

Special Considerations:

- The surface on which the adhesive is to be applied should be clean, dry and free of any surface contamination, such as dust, oil or rust. Isopropyl alcohol would be a recommended solvent to clean the surface.
- Pressure sensitive adhesives should be laminated or applied at warm temperatures (>50F) for optimal adhesion.
- All values shown are averages and should not be used for specification purposes. Adhesion and tack values have a 15% tolerance allotted to the values stated.
- Test data and test results contained in this document are for general information only and shall not be relied upon by POLYONICS customers for designs and specifications, or be relied on as meeting specified performance criteria.
- Customers desiring to develop specifications or performance criteria for specific product applications should contact Polyonics for further information
- Complete removal from substrates may depend on temperature and the duration of time the tape experiences the temperature.

Technical Data

Property	Test Method		XA-1030	XA-1031
Thickness	ASTM D1000			
	Top Paper Liner		3.2 mil (81um)	3.2 mil (81um)
	300 Adhesive - Acrylic		1.1 mil (28um)	1.5 mil (38um)
	Base PET Liner		1.5 mil (36um)	1.5 mil (36um)
Adhesion (stainless)	Polyonics 80313 ¹		1 mil polyimide	2 mil polyimide
	20 minute dwell		>27 oz/in	>35 oz/in
	24 hour dwell		>30 oz/in	>40 oz/in
Shear	SAFT ASTM D4498 ²		190C	190C
Tack	80155		800 g/in	1000 g/in
	1 mil polyimide			
Maximum Temperature ³	Short Term (< 15 min)		Up to 260C	Up to 260C
	Long term (>6 hrs)		Up to 175C	Up to 175C
Shelf Life			1 year when stored below 80F & 60% RH	

- Notes: 1) 180 degree peel adhesion with substrate being 2 mil polyimide film
2) Laminated to 2 mil PET film
3) Maximum temperature is based minimal adhesion loss for dwell time.



Technical Data Sheet
300 Adhesive
Adhesive Transfer Tapes

Polyonics Material Compliance

RoHS (Restriction of Hazardous Substances) EU Directive 2002/95/EC	Limits set forth in Directive 2005/618/EC amending Directive 2002/95/EC
REACH (Registration Evaluation and Authorization of Chemicals) EU Directive 1907/2006/EC	Limits set forth in Directive 1907/2006/EC Article 7 (2)
Halogen Free - Restriction use of Halogen (IEC 61249-2-21)	Limits set forth in International Electrochemical Commission

WARRANTY-LIMITATION

Polyonics' products are sold with the understanding that the Buyer will test them in actual use and determine for him/herself their adaptability to his/her intended uses. Polyonics warrants to the buyer that its products are free from defects in material and workmanship, but limits its obligations under this warranty to replacement of the products shown to Polyonics' satisfaction to have been defective, if the Buyer has complied with the handling, storage and shelf life requirements as specified by Polyonics in applicable materials specifications.

The above warranties extend solely to Buyer and all warranty claims must be made by the Buyer. Rework or Replacement shall neither exceed nor decrease the original warranty period. The term of all warranty periods shall not exceed thirty (30) days from the date of the original shipment.

THE ABOVE WARRANTIES ARE EXCLUSIVE OF AND IN LIEU OF ALL OTHER WARRANTIES, WRITTEN OR ORAL, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE. NO IMPLIED STATUTORY WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE SHALL APPLY. POLYONICS SHALL NOT BE LIABLE EITHER IN TORT OR IN CONTRACT FOR ANY LOSS OR DAMAGE, DIRECT, INCIDENTAL OR CONSEQUENTIAL, ARISING OUT OF THE USE OR INABILITY TO USE THE PRODUCT, OR FROM DELAY IN THE REPLACEMENT OR REPAIR OF PRODUCTS UNDER THE ABOVE WARRANT

Polyonics, Inc.

28 Industrial Park Dr
Westmoreland, N.H. 03467
Ph: +1 603-352-1415
Fax: +1 603-352-1936
1-888- POLYONX (765-9669)
Email: info@polyonics.com
www.polyonics.com

Dongguan

Asia Technical Center Fuwei Mansion Rm 411
Hongtu Road 88, Nancheng District
Dongguan, Guangdong, China 523078
Ph: 86-755-8825-0441
Fax: 86-755-8825-2429
Email: infoasia@polyonics.com
www.polyonics-cn.com